

Compact CANopen® Safety I/O Module – TTC 2038XS

General description

The TTC 2038XS is an I/O slave module which is designed for distributed safety applications that require a high number of PWM outputs in remote locations and cost-sensitive projects. The TTC 2038XS is designed following functional safety standards and is certified by TÜV NORD. It is equipped with Infineon's TriCore™ Aurix™ TC367 CPU and meets the requirements in state-of-the-art safety relevant applications.

The TTC 2038XS is part of a complete and compatible product range for the off-highway and automotive industries. The module is protected by compact automotive style housings which is perfectly suited for harsh operating conditions.

The TTC 2038XS is controlled using the CANopen® Safety protocol. The module provides a wide range of flexible configurable I/Os and allows local current control using PWM outputs.

Specifications

Parameter		Unit
ECU dimensions	147 x 92 x 38	mm
Dimensions for minimum connector release clearance	208 x 92 x 38	mm
Weight	330	g
Connector	1 x 48	pins
Operating temperature	-40 to +85	°C
Operating altitude	0 to 4000	m
Supply voltage	8 to 32	V
Supply current at 12/24V without load	200/100	mA _{max}
Standby current	≤ 0,8	mA _{max}
Total load current	24	A _{max}
Standards		
Functional safety	EN ISO 13849 PL d	
CE	2014/30/EU 2006/42/EC 2011/65/EU	
E-Mark	ECE-R10 Rev.6	
FCC	47 CFR Part 15B, Class A	
EMC	EN ISO 13766-1/-2 EN 61000-6-2 EN 61000-6-4	
ESD	ISO 10605	
Electrical	ISO 16750-2 ISO 7637-2 /-3, limited to 58 V by external load dump protection	
Protection Ratings	EN 60529 IP65 and IP67 ISO 20653 IP6k9k	
Climatic	ISO 16750-4	
Mechanical	ISO 16750-3	
CANopen® Standards	EN50325-5, CiA-401, CiA-305, CiA-301	



Features

CPU Core

- 32-Bit Infineon TriCore™ Aurix™ TC367
- 2 cores (lockstep cores) running at 300 MHz and memory protection for safety-relevant applications
- Floating-Point Unit and Hardware Security Module*

Interfaces

- 1 x CAN FD 50 kbit/s up to 1 Mbit/s
- 4 x SENT

Outputs

- 8 x PWM OUT up to 1 kHz or digital OUT, up to 4 A, high side, with current measurement, alternative use as digital timer IN (0.1 Hz - 20 kHz) configurable pull-up in groups of 2 or analog IN 12 bit, 0 - 32 V with configurable pull-up
- 6 x digital OUT up to 4 A, high side, current sense, alternative use as PVG OUT, 10 - 90% of BAT+ or voltage OUT 0 V - 75 % BAT+ or analog IN 12 bit, 0 - 32 V
- 2 x PWM OUT up to 4 kHz, up to 4 A, low side, current measurement, featuring timer feedback alternative use digital timer IN (0.1 Hz - 20 kHz) or analog IN 12 bit, 0 - 5 V, 0 - 32 V

Inputs

- 8 x analog IN 12 bit, 0 - 5 V, 0 - 25 mA, 0 - 100 kOhm,
- 2 x analog IN 12 bit, 0 - 5 V, 0 - 32 V with configurable pull-up/down
- 2 x digital timer IN (0.1 Hz - 20 kHz), encoder support, configurable pull-up/down, support for 7/14 mA current loop speed-sensor alternative use as analog IN 12 bit, 0 - 32 V, 0 - 25 mA
- 4 x digital timer IN (0.1 Hz - 20 kHz), encoder support, configurable pull-up alternative use as analog IN 12 bit, 0 - 32 V or SENT interface or digital IN for switching to GND and BAT+
- 1 x Terminal 15
- 1 x Wake-Up

Sensor supply

- 1 x sensor supply, 5 V, max. 250 mA

Software

- CANopen® Safety I/O Module software preinstalled

All inputs and outputs supporting analog IN can also be used as digital Input.


All I/Os and interfaces are protected against short circuit to GND and BAT.

Board temperature, sensor supply and supply voltage are monitored by software.

One safety shut-off group for output stages is available.

* Upcoming feature


Block diagram



Housing and connector

Aluminium die-cast housing

1 x 48 pin connector



For further information, including price and availability, please contact products@ttcontrol.com

Subject to changes and corrections. TTC 2038 is a product name of TTControl GmbH. CODESYS® is a registered trademark of CODESYS GmbH. CANopen® and CiA® are registered community trademarks of CAN in Automation). All other trademarks are the property of their respective holders. To the extent possible under applicable law, TTControl hereby disclaims any and all liability for the content and use of this product flyer.